

## HELPING YOU MANAGE VIBRATION

With the FSI power tool timer range you can monitor the actual usage time which can assist you to protect your workforce from potentially hazardous vibration exposure.

FSI power tool timers also help with efficient maintenance, reducing vibration risks and maintenance costs.



<p>Weight including packaging: 0.43Kg</p>	<p><b>PNEUMATIC TOOL TIMER</b></p> <table border="1"> <thead> <tr> <th>Model No.</th> <th>Volume</th> </tr> </thead> <tbody> <tr> <td>TT-P1</td> <td>80cfm</td> </tr> <tr> <td>TT-P2</td> <td>140cfm</td> </tr> </tbody> </table>	Model No.	Volume	TT-P1	80cfm	TT-P2	140cfm																							
Model No.	Volume																													
TT-P1	80cfm																													
TT-P2	140cfm																													
<p>Weight including packaging: 0.45Kg</p>	<p><b>DIRECT WIRE TOOL TIMER</b></p> <table border="1"> <thead> <tr> <th>Model No.</th> <th>Voltage</th> <th>Amps</th> <th>Type</th> </tr> </thead> <tbody> <tr> <td>TT-E1</td> <td>110V</td> <td>16/32</td> <td>wire</td> </tr> <tr> <td></td> <td>230V</td> <td>16/32</td> <td>wire</td> </tr> <tr> <td></td> <td>415V</td> <td>16/32</td> <td>wire</td> </tr> </tbody> </table> <p>Rated to IP44</p>	Model No.	Voltage	Amps	Type	TT-E1	110V	16/32	wire		230V	16/32	wire		415V	16/32	wire													
Model No.	Voltage	Amps	Type																											
TT-E1	110V	16/32	wire																											
	230V	16/32	wire																											
	415V	16/32	wire																											
<p>Up to 210mm length Weight including packaging: 1.06Kg</p>	<p><b>PLUG/SOCKET TOOL TIMER SINGLE PHASE &amp; 3 PHASE</b></p> <table border="1"> <thead> <tr> <th>Model No.</th> <th>Voltage</th> <th>Amps</th> <th>Type</th> </tr> </thead> <tbody> <tr> <td>TT-E2</td> <td>110V</td> <td>16</td> <td>Plug</td> </tr> <tr> <td>TT-E0</td> <td>110V</td> <td>32</td> <td>Plug</td> </tr> <tr> <td>TT-E5</td> <td>230V</td> <td>16</td> <td>Plug</td> </tr> <tr> <td>TT-E6</td> <td>230V</td> <td>32</td> <td>Plug</td> </tr> <tr> <td>TT-E3</td> <td>415V</td> <td>16</td> <td>Plug</td> </tr> <tr> <td>TT-E4</td> <td>415V</td> <td>32</td> <td>Plug</td> </tr> </tbody> </table> <p>Rated to IP44</p>	Model No.	Voltage	Amps	Type	TT-E2	110V	16	Plug	TT-E0	110V	32	Plug	TT-E5	230V	16	Plug	TT-E6	230V	32	Plug	TT-E3	415V	16	Plug	TT-E4	415V	32	Plug	
Model No.	Voltage	Amps	Type																											
TT-E2	110V	16	Plug																											
TT-E0	110V	32	Plug																											
TT-E5	230V	16	Plug																											
TT-E6	230V	32	Plug																											
TT-E3	415V	16	Plug																											
TT-E4	415V	32	Plug																											

- ENABLES EASY MONITORING OF THE DAILY USAGE OF POWER TOOLS
- ALLOWS EFFICIENT & COST EFFECTIVE MANAGEMENT OF PREVENTATIVE MAINTENANCE
- NO EXTERNAL POWER SOURCE REQUIRED
- EASY TO INSTALL
- UNITS CAN BE DESIGNED TO UNIQUE SPECIFICATION



LIGHTWEIGHT  
DURABLE CONSTRUCTION  
FOR HEAVY INDUSTRIAL USE

KEY CONTROLLED RESET TO  
ENSURE TIMING IS  
CONTROLLED BY AUTHORISED  
PERSONNEL ONLY

NO EXTERNAL  
POWER REQUIRED  
- 5 YEAR BATTERY LIFE

NO CALIBRATION  
OR MAINTENANCE  
REQUIRED

